Datasheet

WatchGuard® XTM 330

WITH A NEXT-GENERATION XTM 330 SECURITY SOLUTION, YOUR NETWORK IS:

SECURE

- Application-layer content inspection recognizes & blocks threats that stateful packet firewalls cannot detect.
- Wide-ranging proxy protection provides robust security on HTTP, HTTPS, FTP, SMTP, POP3, DNS, TCP/UDP.
- A suite of security subscriptions boosts protection in critical attack areas for complete threat management.
- Optional Application Control keeps unproductive, inappropriate, and dangerous apps off-limits.

FAST and EFFICIENT

- Up to 850 Mbps firewall throughput and up to 150 Mbps VPN throughput keep data moving.
- Aggregate throughput can reach 70 Mbps, even when security subscriptions are enabled.
- Seven 1-Gigabit Ethernet ports support high-speed LAN backbone infrastructures and gigabit WAN connections.
- Interactive, real-time monitoring and reporting – at no additional charge – give an unprecedented view into network security activity so you can take immediate preventive or corrective actions.
- Includes the "Pro" version of the Fireware XTM operating system for advanced networking features, including VLAN support, multi-WAN load balancing, and dynamic routing.
- Intuitive management console centrally manages all security functions.
- Role-based access control (RBAC) allows lead administrators to create custom roles for granular control.
- Drag-and-drop Branch Office VPN setup – three clicks and your remote office is connected.

FLEXIBLE

- WAN and VPN failover increase performance, redundancy, and reliability.
- Multiple VPN choices (SSL and IPSec) for flexibility in remote access, including support for Apple iOS devices such as the iPhone, iPad, and IPod touch.
- To maximize port utilization, any of the 7 ports can be configured as Internal, External, or Optional.

SCALABLE

- Add powerful security subscriptions to block spam, control dangerous and inappropriate application usage and web surfing, prevent network intrusions, and stop viruses, spyware, and other malware at the gateway.

PREPARED FOR TOMORROW'S CHALLENGES

- Multi-layered, interlocking security protects the network while throughput remains high. No need to compromise protection for strong performance or vice versa.
- Advanced networking features ensure reliability and the flexibility to meet changing business requirements.
- Secure remote connectivity keeps mobile workforce online and productive.
- Monitoring and reporting tools, included at no extra cost, support industry and regulatory compliance, with drill-down functions that make it easy to pinpoint specific activities.

RECOMMENDED FOR SMALL TO MIDSIZE BUSINESSES

WatchGuard XTM 330 appliances deliver a new class of performance-driven security for growing businesses. The XTM 330 offers up to 850 Mbps firewall throughput and security features including full HTTPS inspection, VoIP support, and optional application control.

WHY BUY AN ALL-IN-ONE SOLUTION?

An all-in-one XTM network security solution integrates complete protection while slashing the time and cost associated with managing multiple single-point security products. All security capabilities work together for a holistic, comprehensive approach to network protection. Your IT staff has more time to focus on other areas of network administration, and your business saves money on support and hardware costs.

"WatchGuard makes a **great firewall and security appliance**, and backs it up with **tremendous and personal support.**"

Chet Cromer
President
C2IT Consulting, Inc

SECURITY FEATURES

Firewall	Stateful Packet Inspection, Deep Application Inspection, Proxy Firewall
Application Proxies	HTTP, HTTPS, SMTP, FTP, DNS, TCP, POP3
Threat Protection	Blocks spyware, DoS attacks, fragmented & malformed packets, blended threats & more
VoIP	H.323. SIP, Call Setup and Session Security
Security Subscriptions	Application Control, Reputation Enabled Defense, spamBlocker, WebBlocker, Gateway AntiVirus, Intrusion Prevention Service

VPN & AUTHENTICATION

Encryption	DES, 3DES, AES 128-, 192-, 256-bit
IPSec	SHA-1, MD5, IKE pre-shared key, 3rd party cert
SSL	Thin client, Web exchange
PPTP	Server & Passthrough
VPN Failover	Yes
Single Sign-On	Transparent Active Directory Authentication
XAUTH	Radius, LDAP, Secure LDAP, Windows Active Directory
Other User Authentication	VASCO, RSA SecurID, Web-based, Local, Microsoft Terminal Services and Citrix

THROUGHPUT & CONNECTIONS

Firewall Throughput*	850 Mbps
VPN Throughput*	150 Mbps
XTM Aggregate Throughput*	70 Mbps
Interfaces 10/100/1000	7 copper
I/O Interfaces	1 Serial/2 USB
Nodes Supported (LAN IPs)	Unrestricted
Concurrent Connections	40,000 (bi-directional)
VLANs bridging, tagging, routed mode	75
WSM Licenses (included)	4
Local User Database	500

VPN & AUTHENTICATION

Branch Office VPN Tunnels	50
MUVPN Tunnels IPSec	5/55 (included/max)
MUVPN Tunnels SSL	55

STANDARD NETWORKING

IP Address Assignment	Static, DynDNS, PPPoE, DHCP (server, client, relay)
NAT	Static, dynamic, 1:1, IPSec traversal, policy-based
QoS	8 priority queues, diffserv, modified strict queuing

MANAGEMENT

Management Platform	WatchGuard System Manager v.11 or higher
Alarms and Notifications	SNMP v2/v3, Email, Mgmt. System Alert
Server Support	Logging, Reporting, Quarantine, WebBlocker, Management
Web UI	Supports Windows, Mac, Linux, and Solaris OS with most common browsers
CLI	Includes direct connect and scripting

CERTIFICATIONS

Security	ICSA, FIPS 140-2 and EAL4+ in progress
Safety	NRTL/C, CB
Network	IPv6 Ready Gold (routing)
Hazardous Substance Control	WEEE, RoHS, REACH

*Throughput rates will vary based on environment and configuration. Contact your WatchGuard reseller or call WatchGuard directly (1.800.734.9905) for help determining the right model.

Powered by Fireware® XTM Pro

The XTM 330 appliance ships with the Pro version of the Fireware XTM operating system, providing the advanced networking features* that demanding networks require.

NETWORKING FEATURES	FIREWARE XTM PRO
Routing	Static Dynamic (BGP4, OSPF, RIP v1/v2) Policy-based
NAT	Static, dynamic, 1:1, IPSec traversal
Other Features	Port Independence, Multi-WAN failover Transparent/drop-in mode Multi-WAN load balancing

***High Availability is not currently available on the XTM 330**

Dimensions and Power

Product Dimensions	11.25" x 17" x 1.75" (28.6 x 43.2 x 4.5 cm)
Shipping Dimensions	18" x 21" x 5.25" (45.7 x 53.3 x 13.3 cm)
Shipping Weight	16.1 lbs (7.3 Kg)
AC Power	100-240 VAC Autosensing
Power Consumption	U.S. 50 Watts (max), 171 BTU (max)
Rack Mountable	1U rack mount kit included

Environment

	Operating	Storage
Temperature	32° F to 104° F 0° C to 40° C	-40° F to 158° F -40° C to 70° C
Relative Humidity	10% to 85% non-condensing	10% to 95% non-condensing
Altitude	0 to 9,843 ft at 95° F (3,000 m at 35° C)	0 to 15,000 ft at 95° F (4,570 m at 35° C)
MTBF	51,644 hours @ 77° F (25° C)	

Expert Guidance and Support

A subscription to LiveSecurity® Service is included with every XTM 330 appliance. This provides hardware warranty with advance hardware replacement, technical support, software updates, and concise threat alerts. Renewable in multi-year subscriptions. Find out more at www.watchguard.com/support-programs.

Buy the Bundle and Get the Works!

Get everything you need for complete threat management at a great price with the Security Bundle. Includes XTM 330 appliance, plus Application Control, Intrusion Prevention Service, Reputation Enabled Defense, Gateway AntiVirus, WebBlocker, spamBlocker, and LiveSecurity Plus with 24/7 tech support.

A great deal when you buy together and save!

U.S. SALES 1.800.734.9905 INTERNATIONAL SALES +1.206.613.0895 www.watchguard.com

No express or implied warranties are provided for herein. All specifications are subject to change and expected future products, features or functionality will be provided on an if and when available basis. © 2011 WatchGuard Technologies, Inc. All rights reserved. WatchGuard, the WatchGuard logo, Fireware, and LiveSecurity are either trademarks or registered trademarks of WatchGuard Technologies, Inc. in the United States and/or other countries. All other tradenames are the property of their respective owners. Part No. WGCE66745_110311